



Bringing the future to a home near you

Hardware

Processor Info	FHD 2600 DMIPS Secure SOC with HEVC
Memory DDR	128MB DDR3 (embedded)
Memory NOR Flash	16MB NOR Flash
Front End	DVB-C Annex A/B/C
Modulation (QAM/XPSK/ Roll Off)	64 QAM,256 QAM
Housing LED	2 x single color LED
Dimen w*h*d (mm)	75*18*28
Operating temp.	0 to 40° C
Operating humidity	10 to 95% RH non-condensing
Lifetime	7 years at 25 degrees Celcius
Certificates	National Certificate - CoC/ErP(EU),CA certificate,REACH Compliant,RoHS Compliant

Software

Supported APP OS	Android AOSP,Android ATV,RDK,Linux
Live TV	DVB Live TV
EPG (Electronic Program Guide)	true
DVB Channel	Brazillian Parental Control,CA Parental Control,DVB Parental control,Auto Search - NIT - Home Channel
Channel Update	Update immediately,Update channel list in the background
DVB_Channel_Switching time	less than 2 seconds
DVB number of channels	1000
Subtitle & CC & TT	DVB_Subtitle_EN300743,DVB_Teletext_EN300472,DCII or SCTE-27,Closed_Caption_CEA608,Closed_Caption_CEA708,Superimpose,EWSB with TMCC
CAS (Conditional Access System)	Various CA options available
Loader Features	DVB SSU OTA,CAS vendor defined OTA,USB download

Connectivity

Connectors RF (+shielding)	RF input 1 IEC
Connectors USB	USB 2.0 Type C

Accessories

Cables	USB 2.0 Type C to Type A 5cm
Power Supply_Rating	5V/500mA